KA CASEMENT PUSH OUT

- EUROPEAN DESIGN
- THERMALLY BROKEN / BICOLOR OPTION
- KA SIGNATURE SASH WIDTH
- MULTIPOINT LOCK HADWARE
- CONCEALED HINGES
- INTERNAL HIDDEN FRAME OPTION
- ANTIFALL LIMITING DEVICE OPTION
- LMI DESIGN - MAX DIMENSIONS
  40” WIDTH x 108” HEIGHT at 70 PSF
- SMI DESIGN- MAX DIMENSIONS
  50” WIDTH x 76” HEIGHT at 110 PSF

GLASS OPTIONS

- ✓ LAMINATED
- ✓ INSULATED
- ✓ INSULATED LAMINATED

THERMAL PERFORMANCE

- ✓ TYPE: SINGLE SASH / WIDTH 38” ; HEIGHT 130”
- ✓ GLASS: ¼” SOLARBAN 70 CLEAR + ½” AIR SPACER + ¼” CLEAR + 0.090“ PVB +¼” CLEAR.
  - U FACTOR: 0.36 BTU/(h*f^2*°F)
  - SHGC: 0.17
  - VT: 0.37

HURRICANE AND IMPACT RESISTANT WINDOWS & DOORS

FBC CERTIFICATE
https://unik-windows.com/fbc-casement-out-window

NFRC CERTIFICATE
https://unik-windows.com/nfrc-casement-out-window

LMI - FL# 48028.1
SMI - FL# 48028.2

Uni-K® FENESTRATION