KA WINDOW WALL

- KA SIGNATURE MULLION DESIGN
- HEAD RECEPTOR OPTION
- TRANSOM OPTION
- THERMALLY BROKEN / BICOLOR OPTION
- MALE / FEMALE MULLION OPTION
- ARCHED OPTION

LMI DESIGN - MAX DIMENSIONS
60” WIDTH x 144” HEIGHT at 70 PSF
48” WIDTH x 168” HEIGHT at 57 PSF

SMI DESIGN- MAX DIMENSIONS
60” WIDTH x 108” HEIGHT at 110 PSF
36” WIDTH x 132” HEIGHT at 100 PSF



GLASS OPTIONS

- ✓ LAMINATED
- ✓ INSULATED
- ✓ INSULATED LAMINATED

THERMAL PERFORMANCE

- ✓ TYPE: SINGLE PANEL / WIDTH 55” ; HEIGHT 130”
- ✓ GLASS: ¼” SOLARBAN 70 CLEAR + ½” AIR SPACER + ¼” CLEAR + 0.090 PVB +¼” CLEAR.
  - U FACTOR: 0.33 BTU/(h*f^2*°F)
  - SHGC: 0.24
  - VT: 0.54

HURRICANE AND IMPACT RESISTANT WINDOWS & DOORS

LMI - FL# 48153.1
SMI - FL# 48153.2

FBC CERTIFICATE
https://unik-windows.com/fbc-window-wall-fixed

NFRC CERTIFICATE
https://unik-windows.com/nfrc-window-wall-fixed

Uni-K®
FENESTRATION