KA FRENCH DOOR

- EUROPEAN DESIGN
- SINGLE AND DOUBLE DOOR OPTION
- THERMALLY BROKEN / BICOLOR OPTION
- ARCHED OPERABLE OPTION
- MULTIPOINT LOCK HARDWARE
- CONCEALED HINGE OPTION
- OPTIONAL SMART ACCESS CONTROL

LMI DESIGN - MAX DIMENSIONS
SINGLE DOOR: 47 ”WIDHT x 130“ HEIGHT at 70 PSF
DOUBLE DOOR: 90”WIDHT x 130” HEIGHT at 70 PSF

SMI DESIGN- MAX DIMENSIONS
SINGLE DOOR: 47 ”WIDHT x 108” HEIGHT at 110 PSF

GLASS OPTIONS

- ✓ LAMINATED
- ✓ INSULATED
- ✓ INSULATED LAMINATED

THERMAL PERFORMANCE

- ✓ TYPE: SINGLE DOOR / WIDTH 45” ; HEIGHT 130”
- ✓ GLASS: ¼” SOLARBAN 70 CLEAR + ½” AIR SPACER + ¼” CLEAR + 0.090 PVB +¼” CLEAR.
  - U FACTOR: 0.37 BTU/(h*f^2*°F)
  - SHGC: 0.17
  - VT: 0.3

HURRICANE AND IMPACT RESISTANT WINDOWS & DOORS

LMI - FL# 48030.1
SMI - FL# 48030.2

FBC CERTIFICATE
https://unik-windows.com/fbc-french-door

NFRC CERTIFICATE
https://unik-windows.com/nfrc-french-door

Uni-K®
FENESTRATION