TILT AND TURN

- EUROPEAN DESIGN
- THERMALLY BROKEN / BICOLOR OPTION
- MULTIPOINT LOCK HADWARE
- KA SIGNATURE SASH WIDTH
- INTERNAL HIDDEN FRAME OPTION
- CONCEALED HINGES
- LMI DESIGN - MAX DIMENSIONS
  40” WIDTH x 108” HEIGHT at 70 PSF
- SMI DESIGN- MAX DIMENSIONS
  40” WIDTH x 90” HEIGHT at 110 PSF



GLASS OPTIONS

- ✓ LAMINATED
- ✓ INSULATED
- ✓ INSULATED LAMINATED

THERMAL PERFORMANCE

- ✓ TYPE: SINGLE SASH / WIDTH 38” ; HEIGHT 130”
- ✓ GLASS: ¼” SOLARBAN 70 CLEAR + ½” AIR SPACER + ¼” CLEAR + 0.090“ PVB +¼” CLEAR.
  - U FACTOR: 0.32 BTU/(h*f^2*°F)
  - SHGC: 0.22
  - VT: 0.49

HURRICANE AND IMPACT RESISTANT WINDOWS & DOORS

LMI - FL# 48029.1
SMI - FL# 48029.2

FBC CERTIFICATE
https://unik-windows.com/fbc-tilt-and-turn-window

NFRC CERTIFICATE
https://unik-windows.com/nfrc-tilt-and-turn-window

Uni-K®
FENESTRATION