# KA SGD
# SLIDING GLASS DOOR



- HIDDEN SASH IN THE JAMB
- HIDDEN SASH IN THE HEAD
- HIDDEN SASH IN THE SILL
- ONLY THE INTERLOCKS ARE VISIBLE
- NO VISIBLE HARDWARE OUTSIDE NOR INSIDE
- UP TO 8 TRACKS

LMI DESIGN - MAX PANEL DIMENSIONS
60” WIDTH x 144” HEIGHT at 75 PSF
48” WIDTH x 168” HEIGHT at 56.9 PSF

SMI DESIGN- MAX PANEL DIMENSIONS
60” WIDTH x 120” HEIGHT at 120 PSF
60” WIDTH x 138” HEIGHT at 105.6 PSF

## GLASS OPTIONS

- ✓ LAMINATED
- ✓ INSULATED
- ✓ INSULATED LAMINATED

## THERMAL PERFORMANCE

- ✓ TYPE: SINGLE SASH / WIDTH 38” ; HEIGHT 130”
- ✓ GLASS: ¼” SOLARBAN 70 CLEAR + ½” AIR SPACER + ¼” CLEAR + 0.090“ PVB +¼” CLEAR.
  - U FACTOR: 0.52 BTU/(h*f²*°F)
  - SHGC: 0.25
  - VT: 0.54

**HURRICANE AND IMPACT RESISTANT WINDOWS & DOORS**

FBC CERTIFICATE
https://unik-windows.com/fbc-sgd-door

NFRC CERTIFICATE
https://unik-windows.com/nfrc-sgd-door

LMI - FL# 48152.1 | FL# 48152.3
SMI - FL# 48152.2 | FL# 48152.4

Uni-K® FENESTRATION